

TEMPERATURE-TABLE for PTCR
Higher quality products and lower costs through improved, reliable firing control

Type PTCR - ZTH				Ring Colour : White/Beige	
Ferro no. :		1425250		Dimensions : ± 20 x 10 x 7,0 mm	
Temperature Range °C :		560 - 660°C			

Ring dia-meter	Ring temperature	Ring dia-meter	Ring temperature	Ring dia-meter	Ring temperature	Ring dia-meter	Ring temperature	Ring dia-meter	Ring temperature	Ring dia-meter	Ring temperature
mm	°C	mm	°C	mm	°C	mm	°C	mm	°C	mm	°C
				20,18	559	19,68	624				
				20,17	561	19,67	625				
				20,16	564	19,66	626				
				20,15	566	19,65	627				
				20,14	568	19,64	627				
				20,13	570	19,63	628				
				20,12	572	19,62	629				
				20,11	574	19,61	629				
				20,10	576	19,60	630				
				20,09	578	19,59	631				
				20,08	579	19,58	632				
				20,07	581	19,57	632				
				20,06	583	19,56	633				
				20,05	584	19,55	634				
				20,04	586	19,54	634				
				20,03	587	19,53	635				
				20,02	589	19,52	636				
				20,01	590	19,51	636				
				20,00	592	19,50	637				
				19,99	593	19,49	637				
				19,98	594	19,48	638				
				19,97	595	19,47	639				
				19,96	597	19,46	639				
				19,95	598	19,45	640				
				19,94	599	19,44	640				
				19,93	600	19,43	641				
				19,92	601	19,42	642				
				19,91	603	19,41	642				
				19,90	604	19,40	643				
				19,89	605	19,39	643				
				19,88	606	19,38	644				
				19,87	607	19,37	645				
				19,86	608	19,36	645				
				19,85	609	19,35	646				
				19,84	610	19,34	647				
				19,83	611	19,33	647				
				19,82	612	19,32	648				
				19,81	613	19,31	649				
				19,80	614	19,30	649				
				19,79	615	19,29	650				
				19,78	616	19,28	651				
				19,77	617	19,27	652				
				19,76	617	19,26	653				
				19,75	618	19,25	653				
				19,74	619	19,24	654				
				19,73	620	19,23	655				
				19,72	621	19,22	656				
				19,71	622	19,21	658				
				19,70	623	19,20	659				
				19,69	623	19,19	660				

Powder Batch # :	005 prefired	Batch approved	<i>Jalib</i>
Date :	16/10/2023	Quality Inspection :	

For inquiries :

Customer Service Desk

Phone : +49 69 27116 432

Fax : +49 69 27116 243

