


TEMPERATURE-TABLE for PTCR
 Higher quality products and lower costs through improved, reliable firing control

Type PTCR - ATH	Ring Colour : Grey
Ferro No. : 1439046	Dimensions : ± 20 x 10 x 7,0 mm
Temperature Range °C : 600 - 850°C	

Ring diameter	Ring temperature	Ring diameter	Ring temperature	Ring diameter	Ring temperature	Ring diameter	Ring temperature	Ring diameter	Ring temperature	Ring diameter	Ring temperature
mm	°C	mm	°C	mm	°C	mm	°C	mm	°C	mm	°C
		20,18	597	19,68	682	19,18	727	18,68	770	18,18	815
		20,17	603	19,67	683	19,17	728	18,67	771	18,17	816
		20,16	608	19,66	684	19,16	729	18,66	772	18,16	817
		20,15	612	19,65	685	19,15	730	18,65	773	18,15	818
		20,14	616	19,64	686	19,14	731	18,64	774	18,14	819
		20,13	620	19,63	687	19,13	732	18,63	775	18,13	820
		20,12	623	19,62	688	19,12	733	18,62	776	18,12	820
		20,11	626	19,61	689	19,11	733	18,61	776	18,11	821
		20,10	628	19,60	690	19,10	734	18,60	777	18,10	822
		20,09	631	19,59	691	19,09	735	18,59	778	18,09	823
		20,08	633	19,58	691	19,08	736	18,58	779	18,08	824
		20,07	635	19,57	692	19,07	737	18,57	780	18,07	825
		20,06	637	19,56	693	19,06	738	18,56	781	18,06	826
		20,05	639	19,55	694	19,05	739	18,55	782	18,05	827
		20,04	640	19,54	695	19,04	739	18,54	783	18,04	828
		20,03	642	19,53	696	19,03	740	18,53	783	18,03	829
		20,02	644	19,52	697	19,02	741	18,52	784	18,02	830
		20,01	646	19,51	698	19,01	742	18,51	785	18,01	831
		20,00	649	19,50	699	19,00	743	18,50	786	18,00	832
		19,99	651	19,49	700	18,99	744	18,49	787	17,99	833
		19,98	652	19,48	701	18,98	745	18,48	788	17,98	834
		19,97	653	19,47	702	18,97	745	18,47	789	17,97	835
		19,96	654	19,46	702	18,96	746	18,46	790	17,96	836
		19,95	655	19,45	703	18,95	747	18,45	790	17,95	837
		19,94	656	19,44	704	18,94	748	18,44	791	17,94	838
		19,93	658	19,43	705	18,93	749	18,43	792	17,93	839
		19,92	659	19,42	706	18,92	750	18,42	793	17,92	840
		19,91	660	19,41	707	18,91	751	18,41	794	17,91	841
		19,90	661	19,40	708	18,90	751	18,40	795	17,90	842
		19,89	662	19,39	709	18,89	752	18,39	796	17,89	843
		19,88	663	19,38	710	18,88	753	18,38	797	17,88	844
		19,87	664	19,37	711	18,87	754	18,37	798	17,87	845
		19,86	665	19,36	711	18,86	755	18,36	798	17,86	846
		19,85	666	19,35	712	18,85	756	18,35	799	17,85	847
		19,84	667	19,34	713	18,84	757	18,34	800	17,84	848
		19,83	668	19,33	714	18,83	758	18,33	801	17,83	849
		19,82	669	19,32	715	18,82	758	18,32	802	17,82	850
		19,81	670	19,31	716	18,81	759	18,31	803		
		19,80	670	19,30	717	18,80	760	18,30	804		
		19,79	671	19,29	718	18,79	761	18,29	805		
		19,78	672	19,28	719	18,78	762	18,28	806		
		19,77	673	19,27	719	18,77	763	18,27	807		
		19,76	674	19,26	720	18,76	764	18,26	807		
		19,75	675	19,25	721	18,75	764	18,25	808		
		19,74	676	19,24	722	18,74	765	18,24	809		
		19,73	677	19,23	723	18,73	766	18,23	810		
		19,72	678	19,22	724	18,72	767	18,22	811		
		19,71	679	19,21	725	18,71	768	18,21	812		
		19,70	680	19,20	726	18,70	769	18,20	813		
		19,69	681	19,19	726	18,69	770	18,19	814		

Powder Batch # : 001 prefired	Batch approved
Date : 19/03/2022	Quality Inspection : 

For inquiries :
 Customer Service Desk
 Phone : +49 69 27116 432
 Fax : +49 69 27116 243

