


TEMPERATURE-TABLE for PTCR

Higher quality products and lower costs through improved, reliable firing control

Type PTCR - ETH	Ring Colour : Green
Vibrantz no. : 1409477	Dimensions : ± 20 x 10 x 7,0 mm
Temperature Range °C : 850 - 1100°C	

Ring dia-meter mm	Ring temperature °C	Ring dia-meter mm	Ring temperature °C	Ring dia-meter mm	Ring temperature °C	Ring dia-meter mm	Ring temperature °C	Ring dia-meter mm	Ring temperature °C	Ring dia-meter mm	Ring temperature °C
		19,77	849	19,27	930	18,77	987	18,27	1038	17,77	1091
		19,76	851	19,26	932	18,76	988	18,26	1039	17,76	1092
		19,75	853	19,25	933	18,75	989	18,25	1040	17,75	1093
		19,74	855	19,24	934	18,74	990	18,24	1041	17,74	1094
		19,73	857	19,23	936	18,73	991	18,23	1042	17,73	1095
		19,72	859	19,22	937	18,72	992	18,22	1043	17,72	1096
		19,71	861	19,21	938	18,71	993	18,21	1044	17,71	1097
		19,70	863	19,20	939	18,70	994	18,20	1045	17,70	1098
		19,69	865	19,19	941	18,69	995	18,19	1046	17,69	1099
		19,68	867	19,18	942	18,68	996	18,18	1047	17,68	1100
		19,67	869	19,17	943	18,67	997	18,17	1048		
		19,66	871	19,16	944	18,66	998	18,16	1049		
		19,65	872	19,15	945	18,65	999	18,15	1050		
		19,64	874	19,14	947	18,64	1000	18,14	1051		
		19,63	876	19,13	948	18,63	1001	18,13	1052		
		19,62	878	19,12	949	18,62	1002	18,12	1053		
		19,61	879	19,11	950	18,61	1003	18,11	1054		
		19,60	881	19,10	951	18,60	1004	18,10	1056		
		19,59	883	19,09	953	18,59	1005	18,09	1057		
		19,58	884	19,08	954	18,58	1006	18,08	1058		
		19,57	886	19,07	955	18,57	1007	18,07	1059		
		19,56	888	19,06	956	18,56	1008	18,06	1060		
		19,55	889	19,05	957	18,55	1009	18,05	1061		
		19,54	891	19,04	958	18,54	1010	18,04	1062		
		19,53	893	19,03	959	18,53	1011	18,03	1063		
		19,52	894	19,02	961	18,52	1012	18,02	1064		
		19,51	896	19,01	962	18,51	1013	18,01	1065		
		19,50	897	19,00	963	18,50	1014	18,00	1066		
		19,49	899	18,99	964	18,49	1015	17,99	1067		
		19,48	901	18,98	965	18,48	1016	17,98	1068		
		19,47	902	18,97	966	18,47	1017	17,97	1069		
		19,46	904	18,96	967	18,46	1018	17,96	1071		
		19,45	905	18,95	968	18,45	1019	17,95	1072		
		19,44	907	18,94	969	18,44	1020	17,94	1073		
		19,43	908	18,93	971	18,43	1021	17,93	1074		
		19,42	910	18,92	972	18,42	1022	17,92	1075		
		19,41	911	18,91	973	18,41	1024	17,91	1076		
		19,40	912	18,90	974	18,40	1025	17,90	1077		
		19,39	914	18,89	975	18,39	1026	17,89	1078		
		19,38	915	18,88	976	18,38	1027	17,88	1079		
		19,37	917	18,87	977	18,37	1028	17,87	1080		
		19,36	918	18,86	978	18,36	1029	17,86	1081		
		19,35	920	18,85	979	18,35	1030	17,85	1082		
		19,34	921	18,84	980	18,34	1031	17,84	1084		
		19,33	922	18,83	981	18,33	1032	17,83	1085		
		19,32	924	18,82	982	18,32	1033	17,82	1086		
		19,31	925	18,81	983	18,31	1034	17,81	1087		
		19,30	926	18,80	984	18,30	1035	17,80	1088		
		19,29	928	18,79	985	18,29	1036	17,79	1089		
		19,28	929	18,78	986	18,28	1037	17,78	1090		

Powder Batch # : 94	Batch approved 
Date : 18/09/2025	Quality Inspection :

For inquiries :
 Customer Service Desk
 Phone : +49 69 27116 432
 Fax : +49 69 27116 243

