


**TEMPERATURE-TABLE for PTCR**  
**Higher quality products and lower costs through improved, reliable firing control**

Type PTCR - ETH	Ring Colour : Green
Vibrantz no. : 1409477	Dimensions : ± 20 x 10 x 7,0 mm
Temperature Range °C : 850 - 1100°C	

Ring diameter	Ring temperature	Ring diameter	Ring temperature	Ring diameter	Ring temperature	Ring diameter	Ring temperature	Ring diameter	Ring temperature	Ring diameter	Ring temperature
mm	°C	mm	°C	mm	°C	mm	°C	mm	°C	mm	°C
		19,81	849	19,31	932	18,81	991	18,31	1050		
		19,80	851	19,30	934	18,80	992	18,30	1051		
		19,79	853	19,29	935	18,79	993	18,29	1053		
		19,78	855	19,28	936	18,78	994	18,28	1054		
		19,77	857	19,27	938	18,77	996	18,27	1055		
		19,76	860	19,26	939	18,76	997	18,26	1056		
		19,75	862	19,25	940	18,75	998	18,25	1058		
		19,74	864	19,24	941	18,74	999	18,24	1059		
		19,73	866	19,23	943	18,73	1000	18,23	1060		
		19,72	868	19,22	944	18,72	1001	18,22	1062		
		19,71	870	19,21	945	18,71	1002	18,21	1063		
		19,70	872	19,20	946	18,70	1003	18,20	1064		
		19,69	874	19,19	947	18,69	1005	18,19	1065		
		19,68	875	19,18	949	18,68	1006	18,18	1067		
		19,67	877	19,17	950	18,67	1007	18,17	1068		
		19,66	879	19,16	951	18,66	1008	18,16	1069		
		19,65	881	19,15	952	18,65	1009	18,15	1070		
		19,64	883	19,14	953	18,64	1010	18,14	1072		
		19,63	885	19,13	955	18,63	1012	18,13	1073		
		19,62	886	19,12	956	18,62	1013	18,12	1074		
		19,61	888	19,11	957	18,61	1014	18,11	1076		
		19,60	890	19,10	958	18,60	1015	18,10	1077		
		19,59	891	19,09	959	18,59	1016	18,09	1078		
		19,58	893	19,08	960	18,58	1017	18,08	1079		
		19,57	895	19,07	962	18,57	1019	18,07	1081		
		19,56	896	19,06	963	18,56	1020	18,06	1082		
		19,55	898	19,05	964	18,55	1021	18,05	1083		
		19,54	900	19,04	965	18,54	1022	18,04	1084		
		19,53	901	19,03	966	18,53	1023	18,03	1086		
		19,52	903	19,02	967	18,52	1024	18,02	1087		
		19,51	904	19,01	969	18,51	1026	18,01	1088		
		19,50	906	19,00	970	18,50	1027	18,00	1089		
		19,49	907	18,99	971	18,49	1028	17,99	1091		
		19,48	909	18,98	972	18,48	1029	17,98	1092		
		19,47	910	18,97	973	18,47	1030	17,97	1093		
		19,46	912	18,96	974	18,46	1032	17,96	1094		
		19,45	913	18,95	975	18,45	1033	17,95	1095		
		19,44	915	18,94	976	18,44	1034	17,94	1097		
		19,43	916	18,93	978	18,43	1035	17,93	1098		
		19,42	918	18,92	979	18,42	1036	17,92	1099		
		19,41	919	18,91	980	18,41	1038	17,91	1100		
		19,40	920	18,90	981	18,40	1039				
		19,39	922	18,89	982	18,39	1040				
		19,38	923	18,88	983	18,38	1041				
		19,37	925	18,87	984	18,37	1043				
		19,36	926	18,86	985	18,36	1044				
		19,35	927	18,85	987	18,35	1045				
		19,34	929	18,84	988	18,34	1046				
		19,33	930	18,83	989	18,33	1048				
		19,32	931	18,82	990	18,32	1049				

Powder Batch # : 92	Batch approved
Date : 29/01/2025	Quality Inspection : 

For inquiries :  
 Customer Service Desk  
 Phone : +49 69 27116 432  
 Fax : +49 69 27116 243

