

TEMPERATURE-TABLE for PTCR
Higher quality products and lower costs through improved, reliable firing control

Type PTCR - STH				Ring Colour : Green	
Vibrantz no. :		1400606		Dimensions : ± 20 x 10 x 7,0 mm	
Temperature Range °C :		1130 - 1400°C			

Ring diameter mm	Ring temperature °C	Ring diameter mm	Ring temperature °C	Ring diameter mm	Ring temperature °C	Ring diameter mm	Ring temperature °C	Ring diameter mm	Ring temperature °C	Ring diameter mm	Ring temperature °C
		19,79	1130	19,29	1220	18,79	1284	18,29	1340		
		19,78	1132	19,28	1221	18,78	1285	18,28	1341		
		19,77	1134	19,27	1223	18,77	1286	18,27	1342		
		19,76	1137	19,26	1224	18,76	1288	18,26	1343		
		19,75	1139	19,25	1226	18,75	1289	18,25	1344		
		19,74	1142	19,24	1227	18,74	1290	18,24	1345		
		19,73	1144	19,23	1228	18,73	1291	18,23	1346		
		19,72	1146	19,22	1230	18,72	1292	18,22	1347		
		19,71	1148	19,21	1231	18,71	1294	18,21	1348		
		19,70	1151	19,20	1232	18,70	1295	18,20	1350		
		19,69	1153	19,19	1234	18,69	1296	18,19	1351		
		19,68	1155	19,18	1235	18,68	1297	18,18	1352		
		19,67	1157	19,17	1236	18,67	1298	18,17	1353		
		19,66	1159	19,16	1237	18,66	1300	18,16	1354		
		19,65	1161	19,15	1239	18,65	1301	18,15	1356		
		19,64	1163	19,14	1240	18,64	1302	18,14	1357		
		19,63	1165	19,13	1241	18,63	1303	18,13	1358		
		19,62	1167	19,12	1243	18,62	1304	18,12	1360		
		19,61	1169	19,11	1244	18,61	1305	18,11	1361		
		19,60	1171	19,10	1245	18,60	1306	18,10	1362		
		19,59	1173	19,09	1246	18,59	1308	18,09	1364		
		19,58	1175	19,08	1248	18,58	1309	18,08	1365		
		19,57	1177	19,07	1249	18,57	1310	18,07	1367		
		19,56	1178	19,06	1250	18,56	1311	18,06	1369		
		19,55	1180	19,05	1252	18,55	1312	18,05	1370		
		19,54	1182	19,04	1253	18,54	1313	18,04	1372		
		19,53	1184	19,03	1254	18,53	1314	18,03	1374		
		19,52	1185	19,02	1255	18,52	1315	18,02	1376		
		19,51	1187	19,01	1257	18,51	1316	18,01	1378		
		19,50	1189	19,00	1258	18,50	1317	18,00	1379		
		19,49	1190	18,99	1259	18,49	1319	17,99	1382		
		19,48	1192	18,98	1260	18,48	1320	17,98	1384		
		19,47	1194	18,97	1262	18,47	1321	17,97	1386		
		19,46	1195	18,96	1263	18,46	1322	17,96	1388		
		19,45	1197	18,95	1264	18,45	1323	17,95	1390		
		19,44	1198	18,94	1265	18,44	1324	17,94	1393		
		19,43	1200	18,93	1267	18,43	1325	17,93	1395		
		19,42	1201	18,92	1268	18,42	1326	17,92	1398		
		19,41	1203	18,91	1269	18,41	1327	17,91	1401		
		19,40	1204	18,90	1270	18,40	1328				
		19,39	1206	18,89	1272	18,39	1329				
		19,38	1207	18,88	1273	18,38	1330				
		19,37	1209	18,87	1274	18,37	1331				
		19,36	1210	18,86	1275	18,36	1332				
		19,35	1212	18,85	1277	18,35	1333				
		19,34	1213	18,84	1278	18,34	1334				
		19,33	1215	18,83	1279	18,33	1335				
		19,32	1216	18,82	1280	18,32	1336				
		19,31	1217	18,81	1282	18,31	1337				
		19,30	1219	18,80	1283	18,30	1338				

Powder Batch # :	356	Batch approved	<i>Ravenel</i>
Date :	18/06/2025	Quality Inspection :	

For inquiries :
 Customer Service Desk
 Phone : +49 69 27116 432
 Fax : +49 69 27116 243

