



TEMPERATURE-TABLE for PTCR

Higher quality products and lower costs through improved, reliable firing control

Type PTCR - MTH		Ring Colour : Crème
Vibrantz no. :	1400608	Dimensions : ± 20 x 10 x 7,0 mm
Temperature Range °C :	1340 - 1520°C	

Ring diameter	Ring temperature	Ring diameter	Ring temperature	Ring diameter	Ring temperature	Ring diameter	Ring temperature	Ring diameter	Ring temperature	Ring diameter	Ring temperature
mm	°C	mm	°C	mm	°C	mm	°C	mm	°C	mm	°C
		19,77	1340	19,27	1418	18,77	1444	18,27	1464	17,77	1505
		19,76	1343	19,26	1419	18,76	1445	18,26	1464	17,76	1507
		19,75	1346	19,25	1419	18,75	1445	18,25	1465	17,75	1508
		19,74	1349	19,24	1420	18,74	1445	18,24	1465	17,74	1509
		19,73	1352	19,23	1421	18,73	1446	18,23	1466	17,73	1510
		19,72	1355	19,22	1421	18,72	1446	18,22	1466	17,72	1511
		19,71	1358	19,21	1422	18,71	1447	18,21	1467	17,71	1513
		19,70	1360	19,20	1423	18,70	1447	18,20	1467	17,70	1514
		19,69	1363	19,19	1423	18,69	1447	18,19	1468	17,69	1515
		19,68	1365	19,18	1424	18,68	1448	18,18	1469	17,68	1516
		19,67	1367	19,17	1424	18,67	1448	18,17	1469	17,67	1517
		19,66	1370	19,16	1425	18,66	1449	18,16	1470	17,66	1518
		19,65	1372	19,15	1426	18,65	1449	18,15	1470	17,65	1520
		19,64	1374	19,14	1426	18,64	1449	18,14	1471		
		19,63	1376	19,13	1427	18,63	1450	18,13	1472		
		19,62	1378	19,12	1427	18,62	1450	18,12	1472		
		19,61	1379	19,11	1428	18,61	1450	18,11	1473		
		19,60	1381	19,10	1429	18,60	1451	18,10	1474		
		19,59	1383	19,09	1429	18,59	1451	18,09	1475		
		19,58	1385	19,08	1430	18,58	1451	18,08	1475		
		19,57	1386	19,07	1430	18,57	1452	18,07	1476		
		19,56	1388	19,06	1431	18,56	1452	18,06	1477		
		19,55	1389	19,05	1431	18,55	1453	18,05	1478		
		19,54	1391	19,04	1432	18,54	1453	18,04	1478		
		19,53	1392	19,03	1432	18,53	1453	18,03	1479		
		19,52	1394	19,02	1433	18,52	1454	18,02	1480		
		19,51	1395	19,01	1433	18,51	1454	18,01	1481		
		19,50	1396	19,00	1434	18,50	1454	18,00	1482		
		19,49	1397	18,99	1434	18,49	1455	17,99	1482		
		19,48	1399	18,98	1435	18,48	1455	17,98	1483		
		19,47	1400	18,97	1435	18,47	1455	17,97	1484		
		19,46	1401	18,96	1436	18,46	1456	17,96	1485		
		19,45	1402	18,95	1436	18,45	1456	17,95	1486		
		19,44	1403	18,94	1437	18,44	1457	17,94	1487		
		19,43	1404	18,93	1437	18,43	1457	17,93	1488		
		19,42	1405	18,92	1438	18,42	1457	17,92	1489		
		19,41	1406	18,91	1438	18,41	1458	17,91	1490		
		19,40	1407	18,90	1439	18,40	1458	17,90	1491		
		19,39	1408	18,89	1439	18,39	1459	17,89	1492		
		19,38	1409	18,88	1440	18,38	1459	17,88	1493		
		19,37	1410	18,87	1440	18,37	1459	17,87	1494		
		19,36	1411	18,86	1440	18,36	1460	17,86	1495		
		19,35	1412	18,85	1441	18,35	1460	17,85	1496		
		19,34	1412	18,84	1441	18,34	1461	17,84	1497		
		19,33	1413	18,83	1442	18,33	1461	17,83	1499		
		19,32	1414	18,82	1442	18,32	1461	17,82	1500		
		19,31	1415	18,81	1443	18,31	1462	17,81	1501		
		19,30	1416	18,80	1443	18,30	1462	17,80	1502		
		19,29	1416	18,79	1443	18,29	1463	17,79	1503		
		19,28	1417	18,78	1444	18,28	1463	17,78	1504		

Powder Batch # :	362	Batch approved	
Date :	25/03/2025	Quality Inspection :	

For inquiries :

Customer Service Desk
Phone : +49 69 27116 432
Fax : +49 69 27116 243

