



**TEMPERATURE-TABLE for PTCR**  
Higher quality products and lower costs through improved, reliable firing control

Type PTCR - HTH	Ring Colour : White
Vibrantz no. : 1400610	Dimensions : ± 20 x 10 x 7,0 mm
Temperature Range °C : 1450 - 1750°C	

Ring diameter	Ring temperature	Ring diameter	Ring temperature	Ring diameter	Ring temperature	Ring diameter	Ring temperature	Ring diameter	Ring temperature	Ring diameter	Ring temperature
mm	°C	mm	°C	mm	°C	mm	°C	mm	°C	mm	°C
		19,54	1490	19,04	1584	18,54	1636	18,04	1675	17,54	1728
		19,53	1492	19,03	1585	18,53	1636	18,03	1676	17,53	1729
		19,52	1495	19,02	1586	18,52	1637	18,02	1676	17,52	1730
		19,51	1497	19,01	1588	18,51	1638	18,01	1677	17,51	1732
		19,50	1499	19,00	1589	18,50	1639	18,00	1678	17,50	1733
		19,49	1502	18,99	1590	18,49	1640	17,99	1679	17,49	1735
		19,48	1504	18,98	1592	18,48	1640	17,98	1680	17,48	1736
		19,47	1506	18,97	1593	18,47	1641	17,97	1681	17,47	1737
		19,46	1509	18,96	1594	18,46	1642	17,96	1682	17,46	1739
		19,45	1511	18,95	1595	18,45	1643	17,95	1682	17,45	1740
		19,44	1513	18,94	1596	18,44	1643	17,94	1683	17,44	1742
		19,43	1515	18,93	1598	18,43	1644	17,93	1684	17,43	1743
		19,42	1518	18,92	1599	18,42	1645	17,92	1685	17,42	1745
		19,41	1520	18,91	1600	18,41	1646	17,91	1686	17,41	1746
		19,40	1522	18,90	1601	18,40	1647	17,90	1687	17,40	1748
		19,39	1524	18,89	1602	18,39	1647	17,89	1688	17,39	1750
		19,38	1526	18,88	1603	18,38	1648	17,88	1689		
		19,37	1528	18,87	1605	18,37	1649	17,87	1690		
		19,36	1530	18,86	1606	18,36	1650	17,86	1691		
		19,35	1532	18,85	1607	18,35	1650	17,85	1692		
		19,34	1534	18,84	1608	18,34	1651	17,84	1693		
		19,33	1536	18,83	1609	18,33	1652	17,83	1694		
		19,32	1538	18,82	1610	18,32	1653	17,82	1695		
		19,31	1540	18,81	1611	18,31	1653	17,81	1696		
		19,30	1542	18,80	1612	18,30	1654	17,80	1697		
		19,29	1544	18,79	1613	18,29	1655	17,79	1698		
		19,28	1546	18,78	1614	18,28	1656	17,78	1699		
		19,27	1547	18,77	1615	18,27	1656	17,77	1700		
		19,26	1549	18,76	1616	18,26	1657	17,76	1701		
		19,25	1551	18,75	1617	18,25	1658	17,75	1702		
		19,24	1553	18,74	1618	18,24	1659	17,74	1703		
		19,23	1555	18,73	1619	18,23	1659	17,73	1704		
		19,22	1556	18,72	1620	18,22	1660	17,72	1705		
		19,21	1558	18,71	1621	18,21	1661	17,71	1707		
		19,20	1560	18,70	1622	18,20	1662	17,70	1708		
19,69	1449	19,19	1561	18,69	1623	18,19	1663	17,69	1709		
19,68	1452	19,18	1563	18,68	1624	18,18	1663	17,68	1710		
19,67	1455	19,17	1565	18,67	1624	18,17	1664	17,67	1711		
19,66	1458	19,16	1566	18,66	1625	18,16	1665	17,66	1712		
19,65	1460	19,15	1568	18,65	1626	18,15	1666	17,65	1714		
19,64	1463	19,14	1569	18,64	1627	18,14	1667	17,64	1715		
19,63	1466	19,13	1571	18,63	1628	18,13	1667	17,63	1716		
19,62	1469	19,12	1572	18,62	1629	18,12	1668	17,62	1717		
19,61	1471	19,11	1574	18,61	1630	18,11	1669	17,61	1718		
19,60	1474	19,10	1575	18,60	1631	18,10	1670	17,60	1720		
19,59	1477	19,09	1577	18,59	1631	18,09	1671	17,59	1721		
19,58	1479	19,08	1578	18,58	1632	18,08	1671	17,58	1722		
19,57	1482	19,07	1580	18,57	1633	18,07	1672	17,57	1724		
19,56	1485	19,06	1581	18,56	1634	18,06	1673	17,56	1725		
19,55	1487	19,05	1582	18,55	1635	18,05	1674	17,55	1726		

Powder Batch # : 462	Batch approved
Date : 30/01/2025	Quality Inspection :

For inquiries :  
Customer Service Desk  
Phone : +49 69 27116 432  
Fax : +49 69 27116 243

