



TEMPERATURE-TABLE for PTCR
Higher quality products and lower costs through improved, reliable firing control

| | |
|--------------------------------------|---------------------------------|
| Type PTCR - HTH | Ring Colour : White |
| Vibrantz no. : 1400610 | Dimensions : ± 20 x 10 x 7,0 mm |
| Temperature Range °C : 1450 - 1750°C | |

| Ring dia-meter | Ring tempe-rature | Ring dia-meter | Ring tempe-rature | Ring dia-meter | Ring tempe-rature | Ring dia-meter | Ring tempe-rature | Ring dia-meter | Ring tempe-rature | Ring dia-meter | Ring tempe-rature |
|----------------|-------------------|----------------|-------------------|----------------|-------------------|----------------|-------------------|----------------|-------------------|----------------|-------------------|
| mm | °C | mm | °C | mm | °C | mm | °C | mm | °C | mm | °C |
| | | 19,49 | 1497 | 18,99 | 1591 | 18,49 | 1647 | 17,99 | 1680 | 17,49 | 1723 |
| | | 19,48 | 1500 | 18,98 | 1593 | 18,48 | 1648 | 17,98 | 1680 | 17,48 | 1724 |
| | | 19,47 | 1502 | 18,97 | 1594 | 18,47 | 1648 | 17,97 | 1681 | 17,47 | 1725 |
| | | 19,46 | 1504 | 18,96 | 1596 | 18,46 | 1649 | 17,96 | 1681 | 17,46 | 1727 |
| | | 19,45 | 1506 | 18,95 | 1597 | 18,45 | 1650 | 17,95 | 1682 | 17,45 | 1728 |
| | | 19,44 | 1509 | 18,94 | 1599 | 18,44 | 1651 | 17,94 | 1683 | 17,44 | 1730 |
| | | 19,43 | 1511 | 18,93 | 1600 | 18,43 | 1652 | 17,93 | 1683 | 17,43 | 1731 |
| | | 19,42 | 1513 | 18,92 | 1601 | 18,42 | 1652 | 17,92 | 1684 | 17,42 | 1733 |
| | | 19,41 | 1515 | 18,91 | 1603 | 18,41 | 1653 | 17,91 | 1685 | 17,41 | 1734 |
| | | 19,40 | 1517 | 18,90 | 1604 | 18,40 | 1654 | 17,90 | 1685 | 17,40 | 1736 |
| | | 19,39 | 1520 | 18,89 | 1605 | 18,39 | 1654 | 17,89 | 1686 | 17,39 | 1737 |
| | | 19,38 | 1522 | 18,88 | 1607 | 18,38 | 1655 | 17,88 | 1687 | 17,38 | 1739 |
| | | 19,37 | 1524 | 18,87 | 1608 | 18,37 | 1656 | 17,87 | 1687 | 17,37 | 1740 |
| | | 19,36 | 1526 | 18,86 | 1609 | 18,36 | 1657 | 17,86 | 1688 | 17,36 | 1742 |
| | | 19,35 | 1528 | 18,85 | 1610 | 18,35 | 1657 | 17,85 | 1689 | 17,35 | 1744 |
| | | 19,34 | 1530 | 18,84 | 1612 | 18,34 | 1658 | 17,84 | 1689 | 17,34 | 1745 |
| | | 19,33 | 1532 | 18,83 | 1613 | 18,33 | 1659 | 17,83 | 1690 | 17,33 | 1747 |
| | | 19,32 | 1534 | 18,82 | 1614 | 18,32 | 1659 | 17,82 | 1691 | 17,32 | 1749 |
| | | 19,31 | 1536 | 18,81 | 1615 | 18,31 | 1660 | 17,81 | 1692 | 17,31 | 1751 |
| | | 19,30 | 1538 | 18,80 | 1617 | 18,30 | 1661 | 17,80 | 1692 | | |
| | | 19,29 | 1540 | 18,79 | 1618 | 18,29 | 1661 | 17,79 | 1693 | | |
| | | 19,28 | 1542 | 18,78 | 1619 | 18,28 | 1662 | 17,78 | 1694 | | |
| | | 19,27 | 1544 | 18,77 | 1620 | 18,27 | 1663 | 17,77 | 1695 | | |
| | | 19,26 | 1546 | 18,76 | 1621 | 18,26 | 1663 | 17,76 | 1695 | | |
| | | 19,25 | 1548 | 18,75 | 1622 | 18,25 | 1664 | 17,75 | 1696 | | |
| | | 19,24 | 1550 | 18,74 | 1623 | 18,24 | 1664 | 17,74 | 1697 | | |
| | | 19,23 | 1551 | 18,73 | 1624 | 18,23 | 1665 | 17,73 | 1698 | | |
| | | 19,22 | 1553 | 18,72 | 1626 | 18,22 | 1666 | 17,72 | 1699 | | |
| | | 19,21 | 1555 | 18,71 | 1627 | 18,21 | 1666 | 17,71 | 1700 | | |
| | | 19,20 | 1557 | 18,70 | 1628 | 18,20 | 1667 | 17,70 | 1700 | | |
| 19,69 | 1449 | 19,19 | 1559 | 18,69 | 1629 | 18,19 | 1668 | 17,69 | 1701 | | |
| 19,68 | 1451 | 19,18 | 1561 | 18,68 | 1630 | 18,18 | 1668 | 17,68 | 1702 | | |
| 19,67 | 1454 | 19,17 | 1562 | 18,67 | 1631 | 18,17 | 1669 | 17,67 | 1703 | | |
| 19,66 | 1456 | 19,16 | 1564 | 18,66 | 1632 | 18,16 | 1669 | 17,66 | 1704 | | |
| 19,65 | 1459 | 19,15 | 1566 | 18,65 | 1633 | 18,15 | 1670 | 17,65 | 1705 | | |
| 19,64 | 1461 | 19,14 | 1568 | 18,64 | 1634 | 18,14 | 1671 | 17,64 | 1706 | | |
| 19,63 | 1464 | 19,13 | 1569 | 18,63 | 1635 | 18,13 | 1671 | 17,63 | 1707 | | |
| 19,62 | 1466 | 19,12 | 1571 | 18,62 | 1636 | 18,12 | 1672 | 17,62 | 1708 | | |
| 19,61 | 1469 | 19,11 | 1573 | 18,61 | 1637 | 18,11 | 1672 | 17,61 | 1709 | | |
| 19,60 | 1471 | 19,10 | 1574 | 18,60 | 1637 | 18,10 | 1673 | 17,60 | 1710 | | |
| 19,59 | 1474 | 19,09 | 1576 | 18,59 | 1638 | 18,09 | 1674 | 17,59 | 1711 | | |
| 19,58 | 1476 | 19,08 | 1578 | 18,58 | 1639 | 18,08 | 1674 | 17,58 | 1712 | | |
| 19,57 | 1479 | 19,07 | 1579 | 18,57 | 1640 | 18,07 | 1675 | 17,57 | 1713 | | |
| 19,56 | 1481 | 19,06 | 1581 | 18,56 | 1641 | 18,06 | 1675 | 17,56 | 1714 | | |
| 19,55 | 1483 | 19,05 | 1582 | 18,55 | 1642 | 18,05 | 1676 | 17,55 | 1716 | | |
| 19,54 | 1486 | 19,04 | 1584 | 18,54 | 1643 | 18,04 | 1677 | 17,54 | 1717 | | |
| 19,53 | 1488 | 19,03 | 1585 | 18,53 | 1644 | 18,03 | 1677 | 17,53 | 1718 | | |
| 19,52 | 1490 | 19,02 | 1587 | 18,52 | 1644 | 18,02 | 1678 | 17,52 | 1719 | | |
| 19,51 | 1493 | 19,01 | 1588 | 18,51 | 1645 | 18,01 | 1678 | 17,51 | 1720 | | |
| 19,50 | 1495 | 19,00 | 1590 | 18,50 | 1646 | 18,00 | 1679 | 17,50 | 1722 | | |

| | |
|----------------------|----------------------|
| Powder Batch # : 461 | Batch approved |
| Date : 29/07/2024 | Quality Inspection : |

For inquiries :
Customer Service Desk
Phone : +49 69 27116 432
Fax : +49 69 27116 243

Energy
AFNOR CERTIFICATION

Environment
AFNOR CERTIFICATION

Qualite
AFNOR CERTIFICATION

sheet 367 - 461 - 010

