

测温环外径与温度对照表

产品型号(Type): ZTC 002				规格 (Dimensions): $\Phi_o 20 \times \Phi_i 10 \times h 7\text{mm}$, 橙色 (Orange)			
适用温度范围(Temperature): 500 °C ~ 700 °C				试验条件(Condition): 空气气氛下保温 1 小时			
Φ (mm)	T (°C)	Φ (mm)	T (°C)	Φ (mm)	T (°C)	Φ (mm)	T (°C)
20.01	500	19.56	574	19.11	606	18.66	647
20.00	503	19.55	575	19.10	606	18.65	649
19.99	505	19.54	576	19.09	607	18.64	650
19.98	507	19.53	577	19.08	608	18.63	652
19.97	509	19.52	578	19.07	609	18.62	654
19.96	511	19.51	578	19.06	609	18.61	656
19.95	513	19.50	579	19.05	610	18.60	657
19.94	515	19.49	580	19.04	611	18.59	659
19.93	517	19.48	581	19.03	611	18.58	661
19.92	519	19.47	581	19.02	612	18.57	663
19.91	522	19.46	582	19.01	612	18.56	664
19.90	524	19.45	583	19.00	613	18.55	666
19.89	526	19.44	584	18.99	614	18.54	668
19.88	529	19.43	584	18.98	615	18.53	669
19.87	531	19.42	585	18.97	616	18.52	670
19.86	533	19.41	585	18.96	617	18.51	672
19.85	536	19.40	586	18.95	617	18.50	674
19.84	538	19.39	587	18.94	618	18.49	675
19.83	540	19.38	588	18.93	618	18.48	676
19.82	542	19.37	588	18.92	619	18.47	677
19.81	544	19.36	589	18.91	620	18.46	679
19.80	546	19.35	590	18.90	621	18.45	680
19.79	548	19.34	590	18.89	622	18.44	682
19.78	550	19.33	591	18.88	623	18.43	683
19.77	552	19.32	591	18.87	624	18.42	684
19.76	553	19.31	592	18.86	624	18.41	685
19.75	555	19.30	593	18.85	625	18.40	686
19.74	556	19.29	594	18.84	626	18.39	687
19.73	558	19.28	594	18.83	627	18.38	688
19.72	559	19.27	595	18.82	628	18.37	689
19.71	560	19.26	596	18.81	629	18.36	690
19.70	561	19.25	597	18.80	630	18.35	691
19.69	562	19.24	597	18.79	631	18.34	692
19.68	563	19.23	598	18.78	632	18.33	693
19.67	564	19.22	598	18.77	633	18.32	694
19.66	565	19.21	599	18.76	634	18.31	695
19.65	566	19.20	600	18.75	635	18.30	696
19.64	567	19.19	600	18.74	636	18.29	697
19.63	568	19.18	601	18.73	637	18.28	698
19.62	569	19.17	602	18.72	639	18.27	700
19.61	570	19.16	603	18.71	640		
19.60	571	19.15	603	18.70	641		
19.59	572	19.14	604	18.69	643		
19.58	572	19.13	605	18.68	644		
19.57	573	19.12	605	18.67	645		

检验工程师 (Inspector): 黄满连

生产日期 (Date): 2020-05-13