

## 测温环外径与温度对照表

产品型号(Type): <b>ZTC 004</b>				规格 (Dimensions): $\Phi_o20 \times \Phi_i10 \times h7\text{mm}$ , 橙色 (Orange)			
适用温度范围(Temperature): <b>500 °C ~ 700 °C</b>				试验条件(Condition): 空气气氛下保温 1 小时			
$\Phi$ (mm)	T (°C)	$\Phi$ (mm)	T (°C)	$\Phi$ (mm)	T (°C)	$\Phi$ (mm)	T (°C)
20.10	500	19.75	578	19.40	607	19.05	652
20.09	503	19.74	579	19.39	608	19.04	654
20.08	506	19.73	580	19.38	609	19.03	656
20.07	509	19.72	581	19.37	610	19.02	659
20.06	512	19.71	581	19.36	611	19.01	661
20.05	516	19.70	582	19.35	612	19.00	664
20.04	520	19.69	583	19.34	613	18.99	666
20.03	524	19.68	584	19.33	614	18.98	668
20.02	528	19.67	585	19.32	615	18.97	671
20.01	532	19.66	586	19.31	616	18.96	673
20.00	536	19.65	587	19.30	617	18.95	675
19.99	540	19.64	588	19.29	618	18.94	677
19.98	544	19.63	588	19.28	619	18.93	679
19.97	547	19.62	589	19.27	620	18.92	681
19.96	550	19.61	590	19.26	621	18.91	683
19.95	553	19.60	591	19.25	622	18.90	685
19.94	555	19.59	592	19.24	623	18.89	687
19.93	557	19.58	593	19.23	624	18.88	689
19.92	558	19.57	593	19.22	625	18.87	690
19.91	560	19.56	594	19.21	626	18.86	692
19.90	561	19.55	595	19.20	628	18.85	694
19.89	563	19.54	596	19.19	629	18.84	695
19.88	564	19.53	597	19.18	630	18.83	697
19.87	565	19.52	598	19.17	631	18.82	698
19.86	566	19.51	598	19.16	633	18.81	699
19.85	567	19.50	599	19.15	634		
19.84	569	19.49	600	19.14	636	18.80	701
19.83	570	19.48	601	19.13	637	18.79	702
19.82	571	19.47	602	19.12	639	18.78	703
19.81	572	19.46	603	19.11	640		
19.80	573	19.45	603	19.10	642		
19.79	574	19.44	604	19.09	644		
19.78	575	19.43	605	19.08	646		
19.77	576	19.42	606	19.07	648		
19.76	577	19.41	607	19.06	650		

检验工程师 (Inspector): 黄满连

生产日期 (Date): 2021- 10- 27