

测温环外径与温度对照表

产品型号(Type): ZTC 006				规格 (Dimensions): $\Phi_o.20 \times \Phi_i.10 \times h.7\text{mm}$, 橙色 (Orange)			
适用温度范围(Temperature): 500 °C ~ 700 °C				试验条件(Condition): 空气气氛下保温 1 小时			
Φ (mm)	T (°C)	Φ (mm)	T (°C)	Φ (mm)	T (°C)	Φ (mm)	T (°C)
		19.70	562	19.30	593	18.90	619
		19.69	563	19.29	594	18.89	620
		19.68	564	19.28	595	18.88	621
		19.67	565	19.27	595	18.87	622
		19.66	566	19.26	596	18.86	623
20.05	500	19.65	567	19.25	597	18.85	624
20.04	502	19.64	568	19.24	597	18.84	624
20.03	504	19.63	569	19.23	598	18.83	625
20.02	506	19.62	570	19.22	598	18.82	626
20.01	508	19.61	571	19.21	599	18.81	627
20.00	510	19.60	572	19.20	600	18.80	628
19.99	512	19.59	572	19.19	600	18.79	628
19.98	514	19.58	573	19.18	601	18.78	629
19.97	515	19.57	574	19.17	602	18.77	630
19.96	517	19.56	575	19.16	602	18.76	631
19.95	519	19.55	576	19.15	603	18.75	632
19.94	521	19.54	576	19.14	603	18.74	633
19.93	523	19.53	577	19.13	604	18.73	634
19.92	525	19.52	578	19.12	605	18.72	635
19.91	527	19.51	579	19.11	605	18.71	636
19.90	529	19.50	580	19.10	606	18.70	637
19.89	531	19.49	581	19.09	607	18.69	638
19.88	533	19.48	581	19.08	607	18.68	639
19.87	535	19.47	582	19.07	608	18.67	640
19.86	537	19.46	583	19.06	609	18.66	641
19.85	539	19.45	583	19.05	609	18.65	642
19.84	541	19.44	584	19.04	610	18.64	643
19.83	543	19.43	585	19.03	611	18.63	645
19.82	544	19.42	586	19.02	611	18.62	646
19.81	546	19.41	586	19.01	612	18.61	647
19.80	548	19.40	587	19.00	612	18.60	649
19.79	550	19.39	588	18.99	613	18.59	650
19.78	551	19.38	588	18.98	614	18.58	652
19.77	553	19.37	589	18.97	614	18.57	653
19.76	554	19.36	589	18.96	615	18.56	654
19.75	555	19.35	590	18.95	616	18.55	656
19.74	557	19.34	591	18.94	617	18.54	658
19.73	558	19.33	591	18.93	617	18.53	659
19.72	559	19.32	592	18.92	618	18.52	661
19.71	560	19.31	593	18.91	619	18.51	662
						18.20	699
						18.19	701

检验工程师 (Inspector): 黄满连

生产日期 (Date): 2025-03-11