

## 测温环外径与温度对照表

产品型号(Type): <b>BTC 012</b>				规格 (Dimensions): $\Phi_o 20 \times \Phi_i 10 \times h 7\text{mm}$ , 浅绿 (Light green)			
适用温度范围(Temperature): <b>900 °C ~ 1200 °C</b>				试验条件(Condition): 空气气氛下保温 1 小时			
$\Phi$ (mm)	T (°C)	$\Phi$ (mm)	T (°C)	$\Phi$ (mm)	T (°C)	$\Phi$ (mm)	T (°C)
19.88	897	19.43	1013	18.98	1084	18.53	1134
19.87	901	19.42	1015	18.97	1085	18.52	1135
19.86	905	19.41	1017	18.96	1087	18.51	1136
19.85	909	19.40	1018	18.95	1088	18.50	1137
19.84	913	19.39	1020	18.94	1089	18.49	1138
19.83	917	19.38	1022	18.93	1090	18.48	1139
19.82	920	19.37	1023	18.92	1092	18.47	1140
19.81	923	19.36	1025	18.91	1093	18.46	1140
19.80	927	19.35	1026	18.90	1094	18.45	1141
19.79	930	19.34	1028	18.89	1095	18.44	1142
19.78	934	19.33	1030	18.88	1097	18.43	1143
19.77	937	19.32	1032	18.87	1098	18.42	1144
19.76	940	19.31	1034	18.86	1099	18.41	1145
19.75	943	19.30	1036	18.85	1100	18.40	1145
19.74	946	19.29	1037	18.84	1101	18.39	1146
19.73	949	19.28	1039	18.83	1103	18.38	1147
19.72	951	19.27	1040	18.82	1105	18.37	1148
19.71	954	19.26	1042	18.81	1106	18.36	1149
19.70	957	19.25	1043	18.80	1107	18.35	1150
19.69	960	19.24	1045	18.79	1108	18.34	1151
19.68	962	19.23	1046	18.78	1109	18.33	1152
19.67	965	19.22	1048	18.77	1110	18.32	1153
19.66	967	19.21	1050	18.76	1111	18.31	1154
19.65	969	19.20	1052	18.75	1112	18.30	1154
19.64	971	19.19	1054	18.74	1113	18.29	1155
19.63	973	19.18	1055	18.73	1114	18.28	1156
19.62	976	19.17	1057	18.72	1115	18.27	1157
19.61	978	19.16	1058	18.71	1116	18.26	1157
19.60	981	19.15	1060	18.70	1117	18.25	1158
19.59	983	19.14	1061	18.69	1118	18.24	1159
19.58	985	19.13	1062	18.68	1119	18.23	1160
19.57	987	19.12	1064	18.67	1120	18.22	1160
19.56	989	19.11	1065	18.66	1121	18.21	1161
19.55	991	19.10	1067	18.65	1122	18.20	1162
19.54	993	19.09	1068	18.64	1123	18.19	1163
19.53	994	19.08	1070	18.63	1124	18.18	1163
19.52	996	19.07	1071	18.62	1125	18.17	1164
19.51	998	19.06	1072	18.61	1127	18.16	1165
19.50	1000	19.05	1074	18.60	1128	18.15	1165
19.49	1002	19.04	1075	18.59	1129	18.14	1166
19.48	1004	19.03	1077	18.58	1130	18.13	1167
19.47	1006	19.02	1079	18.57	1131	18.12	1168
19.46	1008	19.01	1080	18.56	1132	18.11	1168
19.45	1010	19.00	1081	18.55	1133	18.10	1169
19.44	1011	18.99	1083	18.54	1134	18.09	1170
							17.68 1199
							17.67 1200

检验工程师 (Inspector): 黄满连

生产日期 (Date): 2022-12-15