

测温环外径与温度对照表

| 产品型号(Type): DTC 014 | | | | | | 规格 (Dimensions): $\Phi_o 20 \times \Phi_i 10 \times h 7\text{mm}$, 绿色 (Green) | | | | | |
|---|--------|-------------|--------|-------------|--------|--|--------|-------------|--------|-------------|--------|
| 适用温度范围(Temperature): 1300 °C ~ 1600 °C | | | | | | 试验条件(Condition): 空气气氛下保温 1 小时 | | | | | |
| Φ (mm) | T (°C) | Φ (mm) | T (°C) | Φ (mm) | T (°C) | Φ (mm) | T (°C) | Φ (mm) | T (°C) | Φ (mm) | T (°C) |
| 19.20 | 1300 | 18.75 | 1373 | 18.30 | 1427 | 17.85 | 1478 | 17.40 | 1522 | 16.95 | 1554 |
| 19.19 | 1301 | 18.74 | 1374 | 18.29 | 1429 | 17.84 | 1479 | 17.39 | 1523 | 16.94 | 1554 |
| 19.18 | 1302 | 18.73 | 1376 | 18.28 | 1430 | 17.83 | 1480 | 17.38 | 1524 | 16.93 | 1555 |
| 19.17 | 1303 | 18.72 | 1377 | 18.27 | 1431 | 17.82 | 1481 | 17.37 | 1524 | 16.92 | 1556 |
| 19.16 | 1304 | 18.71 | 1378 | 18.26 | 1432 | 17.81 | 1482 | 17.36 | 1525 | 16.91 | 1557 |
| 19.15 | 1306 | 18.70 | 1380 | 18.25 | 1433 | 17.80 | 1483 | 17.35 | 1526 | 16.90 | 1557 |
| 19.14 | 1307 | 18.69 | 1381 | 18.24 | 1434 | 17.79 | 1484 | 17.34 | 1527 | 16.89 | 1558 |
| 19.13 | 1308 | 18.68 | 1383 | 18.23 | 1435 | 17.78 | 1485 | 17.33 | 1527 | 16.88 | 1559 |
| 19.12 | 1310 | 18.67 | 1384 | 18.22 | 1436 | 17.77 | 1486 | 17.32 | 1528 | 16.87 | 1560 |
| 19.11 | 1311 | 18.66 | 1385 | 18.21 | 1437 | 17.76 | 1487 | 17.31 | 1528 | 16.86 | 1561 |
| 19.10 | 1313 | 18.65 | 1387 | 18.20 | 1438 | 17.75 | 1489 | 17.30 | 1529 | 16.85 | 1561 |
| 19.09 | 1314 | 18.64 | 1388 | 18.19 | 1439 | 17.74 | 1490 | 17.29 | 1530 | 16.84 | 1562 |
| 19.08 | 1316 | 18.63 | 1389 | 18.18 | 1440 | 17.73 | 1491 | 17.28 | 1531 | 16.83 | 1563 |
| 19.07 | 1317 | 18.62 | 1391 | 18.17 | 1441 | 17.72 | 1492 | 17.27 | 1531 | 16.82 | 1564 |
| 19.06 | 1319 | 18.61 | 1392 | 18.16 | 1442 | 17.71 | 1493 | 17.26 | 1532 | 16.81 | 1565 |
| 19.05 | 1321 | 18.60 | 1393 | 18.15 | 1444 | 17.70 | 1494 | 17.25 | 1533 | 16.80 | 1565 |
| 19.04 | 1322 | 18.59 | 1395 | 18.14 | 1445 | 17.69 | 1495 | 17.24 | 1534 | 16.79 | 1566 |
| 19.03 | 1324 | 18.58 | 1396 | 18.13 | 1446 | 17.68 | 1496 | 17.23 | 1535 | 16.78 | 1567 |
| 19.02 | 1325 | 18.57 | 1397 | 18.12 | 1447 | 17.67 | 1497 | 17.22 | 1535 | 16.77 | 1568 |
| 19.01 | 1327 | 18.56 | 1399 | 18.11 | 1448 | 17.66 | 1498 | 17.21 | 1536 | 16.76 | 1569 |
| 19.00 | 1329 | 18.55 | 1400 | 18.10 | 1449 | 17.65 | 1499 | 17.20 | 1537 | 16.75 | 1569 |
| 18.99 | 1331 | 18.54 | 1401 | 18.09 | 1450 | 17.64 | 1500 | 17.19 | 1537 | 16.74 | 1570 |
| 18.98 | 1332 | 18.53 | 1402 | 18.08 | 1451 | 17.63 | 1501 | 17.18 | 1538 | 16.73 | 1571 |
| 18.97 | 1334 | 18.52 | 1403 | 18.07 | 1452 | 17.62 | 1502 | 17.17 | 1539 | 16.72 | 1572 |
| 18.96 | 1336 | 18.51 | 1404 | 18.06 | 1453 | 17.61 | 1503 | 17.16 | 1539 | 16.71 | 1573 |
| 18.95 | 1338 | 18.50 | 1406 | 18.05 | 1455 | 17.60 | 1504 | 17.15 | 1540 | 16.70 | 1574 |
| 18.94 | 1340 | 18.49 | 1407 | 18.04 | 1456 | 17.59 | 1505 | 17.14 | 1541 | 16.69 | 1575 |
| 18.93 | 1342 | 18.48 | 1408 | 18.03 | 1457 | 17.58 | 1506 | 17.13 | 1542 | 16.68 | 1576 |
| 18.92 | 1344 | 18.47 | 1409 | 18.02 | 1458 | 17.57 | 1507 | 17.12 | 1542 | 16.67 | 1577 |
| 18.91 | 1345 | 18.46 | 1410 | 18.01 | 1459 | 17.56 | 1508 | 17.11 | 1543 | 16.66 | 1578 |
| 18.90 | 1347 | 18.45 | 1411 | 18.00 | 1460 | 17.55 | 1509 | 17.10 | 1543 | 16.65 | 1579 |
| 18.89 | 1349 | 18.44 | 1412 | 17.99 | 1461 | 17.54 | 1510 | 17.09 | 1544 | 16.64 | 1580 |
| 18.88 | 1351 | 18.43 | 1414 | 17.98 | 1463 | 17.53 | 1511 | 17.08 | 1545 | 16.63 | 1581 |
| 18.87 | 1353 | 18.42 | 1415 | 17.97 | 1464 | 17.52 | 1512 | 17.07 | 1546 | 16.62 | 1583 |
| 18.86 | 1355 | 18.41 | 1416 | 17.96 | 1465 | 17.51 | 1512 | 17.06 | 1546 | 16.61 | 1584 |
| 18.85 | 1356 | 18.40 | 1417 | 17.95 | 1466 | 17.50 | 1513 | 17.05 | 1547 | 16.60 | 1585 |
| 18.84 | 1358 | 18.39 | 1418 | 17.94 | 1467 | 17.49 | 1514 | 17.04 | 1548 | 16.59 | 1587 |
| 18.83 | 1359 | 18.38 | 1419 | 17.93 | 1468 | 17.48 | 1515 | 17.03 | 1548 | 16.58 | 1588 |
| 18.82 | 1361 | 18.37 | 1420 | 17.92 | 1469 | 17.47 | 1516 | 17.02 | 1549 | 16.57 | 1590 |
| 18.81 | 1363 | 18.36 | 1421 | 17.91 | 1470 | 17.46 | 1517 | 17.01 | 1550 | 16.56 | 1591 |
| 18.80 | 1365 | 18.35 | 1422 | 17.90 | 1471 | 17.45 | 1518 | 17.00 | 1550 | 16.55 | 1593 |
| 18.79 | 1366 | 18.34 | 1423 | 17.89 | 1473 | 17.44 | 1519 | 16.99 | 1551 | 16.54 | 1595 |
| 18.78 | 1368 | 18.33 | 1424 | 17.88 | 1474 | 17.43 | 1520 | 16.98 | 1552 | 16.53 | 1596 |
| 18.77 | 1370 | 18.32 | 1425 | 17.87 | 1475 | 17.42 | 1520 | 16.97 | 1553 | 16.52 | 1598 |
| 18.76 | 1371 | 18.31 | 1426 | 17.86 | 1476 | 17.41 | 1521 | 16.96 | 1553 | 16.51 | 1599 |

检验工程师 (Inspector): 黄满连

生产日期 (Date): 2024 - 1 - 9