

## 测温环外径与温度对照表

产品型号(Type): <b>DTC 005</b>					规格 (Dimensions): $\Phi_o 20 \times \Phi_i 10 \times h 7\text{mm}$ , 绿色 (Green)						
适用温度范围(Temperature): <b>1300 °C ~ 1600 °C</b>					试验条件(Condition): 空气气氛下保温 1 小时						
$\Phi$ (mm)	T (°C)	$\Phi$ (mm)	T (°C)	$\Phi$ (mm)	T (°C)	$\Phi$ (mm)	T (°C)	$\Phi$ (mm)	T (°C)		
		18.96	1359	18.51	1423	18.06	1481	17.61	1525	17.16	1558
		18.95	1361	18.50	1424	18.05	1482	17.60	1526	17.15	1559
		18.94	1363	18.49	1426	18.04	1483	17.59	1526	17.14	1560
		18.93	1364	18.48	1427	18.03	1485	17.58	1527	17.13	1561
		18.92	1366	18.47	1428	18.02	1486	17.57	1528	17.12	1562
		18.91	1368	18.46	1429	18.01	1487	17.56	1529	17.11	1563
		18.90	1370	18.45	1431	18.00	1488	17.55	1530	17.10	1564
		18.89	1372	18.44	1432	17.99	1489	17.54	1530	17.09	1565
		18.88	1374	18.43	1433	17.98	1490	17.53	1531	17.08	1566
		18.87	1376	18.42	1434	17.97	1491	17.52	1531	17.07	1567
19.31	1299	18.86	1377	18.41	1435	17.96	1493	17.51	1532	17.06	1569
19.30	1300	18.85	1378	18.40	1436	17.95	1494	17.50	1533	17.05	1570
19.29	1302	18.84	1380	18.39	1438	17.94	1495	17.49	1533	17.04	1571
19.28	1303	18.83	1381	18.38	1439	17.93	1496	17.48	1534	17.03	1572
19.27	1304	18.82	1383	18.37	1440	17.92	1497	17.47	1535	17.02	1573
19.26	1306	18.81	1384	18.36	1442	17.91	1498	17.46	1536	17.01	1574
19.25	1307	18.80	1386	18.35	1443	17.90	1499	17.45	1537	17.00	1575
19.24	1308	18.79	1388	18.34	1445	17.89	1500	17.44	1537	16.99	1577
19.23	1309	18.78	1389	18.33	1446	17.88	1501	17.43	1538	16.98	1578
19.22	1311	18.77	1391	18.32	1447	17.87	1502	17.42	1539	16.97	1580
19.21	1312	18.76	1392	18.31	1448	17.86	1503	17.41	1540	16.96	1582
19.20	1314	18.75	1393	18.30	1449	17.85	1504	17.40	1540	16.95	1583
19.19	1316	18.74	1394	18.29	1450	17.84	1505	17.39	1541	16.94	1585
19.18	1317	18.73	1396	18.28	1452	17.83	1506	17.38	1542	16.93	1586
19.17	1319	18.72	1397	18.27	1453	17.82	1507	17.37	1543	16.92	1588
19.16	1321	18.71	1398	18.26	1455	17.81	1508	17.36	1543	16.91	1590
19.15	1323	18.70	1400	18.25	1456	17.80	1509	17.35	1544	16.90	1591
19.14	1324	18.69	1401	18.24	1457	17.79	1510	17.34	1544	16.89	1593
19.13	1325	18.68	1403	18.23	1459	17.78	1511	17.33	1545	16.88	1594
19.12	1327	18.67	1404	18.22	1460	17.77	1512	17.32	1546	16.87	1596
19.11	1329	18.66	1405	18.21	1461	17.76	1513	17.31	1547	16.86	1597
19.10	1331	18.65	1406	18.20	1462	17.75	1514	17.30	1547	16.85	1598
19.09	1333	18.64	1407	18.19	1464	17.74	1514	17.29	1548	16.84	1599
19.08	1335	18.63	1408	18.18	1465	17.73	1515	17.28	1549	16.83	1599
19.07	1337	18.62	1410	18.17	1466	17.72	1516	17.27	1550	16.82	1600
19.06	1339	18.61	1411	18.16	1468	17.71	1516	17.26	1551		
19.05	1341	18.60	1412	18.15	1469	17.70	1517	17.25	1551		
19.04	1343	18.59	1414	18.14	1471	17.69	1518	17.24	1552		
19.03	1345	18.58	1415	18.13	1472	17.68	1519	17.23	1553		
19.02	1347	18.57	1416	18.12	1474	17.67	1520	17.22	1554		
19.01	1349	18.56	1417	18.11	1475	17.66	1521	17.21	1555		
19.00	1351	18.55	1418	18.10	1476	17.65	1521	17.20	1556		
18.99	1353	18.54	1419	18.09	1477	17.64	1522	17.19	1557		
18.98	1355	18.53	1420	18.08	1478	17.63	1523	17.18	1557		
18.97	1357	18.52	1422	18.07	1479	17.62	1524	17.17	1558		

检验工程师 (Inspector): 黄满连

生产日期 (Date): 2018 - 07 - 31