

测温环外径与温度对照表

产品型号(Type): ETC 010				规格 (Dimensions): $\Phi_o 20 \times \Phi_i 10 \times h 7\text{mm}$, 兰色 (Blue)					
适用温度范围(Temperature): 1450 °C ~ 1750 °C				试验条件(Condition): 空气气氛下保温 1 小时					
Φ (mm)	T (°C)	Φ (mm)	T (°C)	Φ (mm)	T (°C)	Φ (mm)	T (°C)	Φ (mm)	T (°C)
		19.02	1538	18.57	1601	18.12	1654	17.67	1700
		19.01	1539	18.56	1602	18.11	1655	17.66	1701
		19.00	1541	18.55	1604	18.10	1656	17.65	1702
		18.99	1543	18.54	1605	18.09	1657	17.64	1704
		18.98	1544	18.53	1606	18.08	1658	17.63	1705
19.42	1448	18.97	1546	18.52	1608	18.07	1659	17.62	1706
19.41	1451	18.96	1547	18.51	1609	18.06	1660	17.61	1708
19.40	1454	18.95	1549	18.50	1610	18.05	1661	17.60	1710
19.39	1457	18.94	1550	18.49	1612	18.04	1662	17.59	1712
19.38	1460	18.93	1551	18.48	1613	18.03	1663	17.58	1713
19.37	1463	18.92	1553	18.47	1614	18.02	1664	17.57	1715
19.36	1466	18.91	1554	18.46	1615	18.01	1665	17.56	1717
19.35	1469	18.90	1556	18.45	1616	18.00	1666	17.55	1719
19.34	1472	18.89	1557	18.44	1618	17.99	1667	17.54	1721
19.33	1475	18.88	1559	18.43	1619	17.98	1668	17.53	1723
19.32	1478	18.87	1560	18.42	1620	17.97	1669	17.52	1725
19.31	1480	18.86	1561	18.41	1621	17.96	1670	17.51	1727
19.30	1483	18.85	1563	18.40	1623	17.95	1671	17.50	1729
19.29	1486	18.84	1565	18.39	1624	17.94	1672	17.49	1731
19.28	1488	18.83	1566	18.38	1625	17.93	1672	17.48	1732
19.27	1491	18.82	1567	18.37	1627	17.92	1673	17.47	1734
19.26	1493	18.81	1568	18.36	1628	17.91	1674	17.46	1735
19.25	1495	18.80	1570	18.35	1629	17.90	1675	17.45	1737
19.24	1497	18.79	1572	18.34	1630	17.89	1676	17.44	1738
19.23	1499	18.78	1573	18.33	1631	17.88	1677	17.43	1739
19.22	1501	18.77	1574	18.32	1632	17.87	1678	17.42	1740
19.21	1503	18.76	1576	18.31	1634	17.86	1679	17.41	1741
19.20	1505	18.75	1577	18.30	1635	17.85	1680	17.40	1742
19.19	1507	18.74	1579	18.29	1636	17.84	1681	17.39	1743
19.18	1509	18.73	1580	18.28	1637	17.83	1682	17.38	1744
19.17	1511	18.72	1581	18.27	1638	17.82	1683	17.37	1745
19.16	1513	18.71	1583	18.26	1639	17.81	1684	17.36	1746
19.15	1515	18.70	1584	18.25	1640	17.80	1685	17.35	1746
19.14	1517	18.69	1585	18.24	1641	17.79	1686	17.34	1747
19.13	1519	18.68	1587	18.23	1642	17.78	1687	17.33	1748
19.12	1520	18.67	1588	18.22	1643	17.77	1688		
19.11	1522	18.66	1589	18.21	1645	17.76	1689	17.32	1749
19.10	1524	18.65	1591	18.20	1646	17.75	1690	17.31	1749
19.09	1526	18.64	1592	18.19	1647	17.74	1691	17.30	1750
19.08	1528	18.63	1593	18.18	1648	17.73	1692	17.29	1750
19.07	1529	18.62	1594	18.17	1649	17.72	1693		
19.06	1531	18.61	1596	18.16	1650	17.71	1694		
19.05	1532	18.60	1597	18.15	1651	17.70	1695		
19.04	1534	18.59	1598	18.14	1652	17.69	1697		
19.03	1536	18.58	1600	18.13	1653	17.68	1698		

检验工程师 (Inspector): 黄满连

生产日期 (Date): 2020 - 12-17