

测温环外径与温度对照表

产品型号(Type): FTC 002				规格 (Dimensions): $\Phi_o 20 \times \Phi_i 10 \times h 7\text{mm}$, 白色(White)					
适用温度范围(Temperature): 1650 °C ~ 1900 °C				试验条件(Condition): 保温 1 小时					
Φ (mm)	T (°C)	Φ (mm)	T (°C)	Φ (mm)	T (°C)	Φ (mm)	T (°C)	Φ (mm)	T (°C)
18.87	1648	18.42	1721	17.97	1770	17.52	1814	17.07	1858
18.86	1650	18.41	1723	17.96	1771	17.51	1815	17.06	1859
18.85	1652	18.40	1724	17.95	1771	17.50	1816	17.05	1860
18.84	1653	18.39	1725	17.94	1772	17.49	1817	17.04	1861
18.83	1654	18.38	1726	17.93	1773	17.48	1818	17.03	1862
18.82	1656	18.37	1727	17.92	1774	17.47	1819	17.02	1863
18.81	1658	18.36	1729	17.91	1775	17.46	1820	17.01	1864
18.80	1659	18.35	1730	17.90	1776	17.45	1821	17.00	1865
18.79	1660	18.34	1731	17.89	1777	17.44	1822	16.99	1866
18.78	1662	18.33	1732	17.88	1778	17.43	1823	16.98	1867
18.77	1663	18.32	1734	17.87	1779	17.42	1824	16.97	1868
18.76	1664	18.31	1735	17.86	1780	17.41	1825	16.96	1869
18.75	1666	18.30	1736	17.85	1781	17.40	1826	16.95	1870
18.74	1668	18.29	1737	17.84	1782	17.39	1827	16.94	1871
18.73	1669	18.28	1738	17.83	1783	17.38	1828	16.93	1872
18.72	1670	18.27	1739	17.82	1784	17.37	1829	16.92	1873
18.71	1672	18.26	1741	17.81	1785	17.36	1830	16.91	1874
18.70	1674	18.25	1742	17.80	1786	17.35	1831	16.90	1875
18.69	1675	18.24	1743	17.79	1787	17.34	1832	16.89	1876
18.68	1677	18.23	1744	17.78	1788	17.33	1833	16.88	1877
18.67	1679	18.22	1745	17.77	1789	17.32	1834	16.87	1878
18.66	1681	18.21	1746	17.76	1790	17.31	1835	16.86	1879
18.65	1683	18.20	1747	17.75	1791	17.30	1836	16.85	1881
18.64	1684	18.19	1748	17.74	1792	17.29	1837	16.84	1882
18.63	1686	18.18	1749	17.73	1793	17.28	1838	16.83	1883
18.62	1688	18.17	1750	17.72	1794	17.27	1839	16.82	1884
18.61	1690	18.16	1751	17.71	1795	17.26	1840	16.81	1885
18.60	1692	18.15	1752	17.70	1796	17.25	1841	16.80	1886
18.59	1693	18.14	1753	17.69	1797	17.24	1842	16.79	1887
18.58	1695	18.13	1754	17.68	1798	17.23	1843	16.78	1888
18.57	1697	18.12	1755	17.67	1799	17.22	1844	16.77	1889
18.56	1699	18.11	1756	17.66	1800	17.21	1845	16.76	1891
18.55	1701	18.10	1757	17.65	1801	17.20	1846	16.75	1892
18.54	1703	18.09	1758	17.64	1802	17.19	1847	16.74	1893
18.53	1704	18.08	1759	17.63	1803	17.18	1848	16.73	1894
18.52	1706	18.07	1760	17.62	1804	17.17	1849	16.72	1895
18.51	1708	18.06	1761	17.61	1805	17.16	1849	16.71	1897
18.50	1709	18.05	1762	17.60	1806	17.15	1850	16.70	1898
18.49	1711	18.04	1763	17.59	1807	17.14	1851	16.69	1899
18.48	1713	18.03	1764	17.58	1808	17.13	1852	16.68	1900
18.47	1714	18.02	1765	17.57	1809	17.12	1853		
18.46	1716	18.01	1766	17.56	1810	17.11	1854		
18.45	1717	18.00	1767	17.55	1811	17.10	1855		
18.44	1718	17.99	1768	17.54	1812	17.09	1856		
18.43	1720	17.98	1769	17.53	1813	17.08	1857		

检验工程师 (Inspector): 黄满连

生产日期 (Date): 2021-04-07