

测温环外径与温度对照表

产品型号(Type): FTC 003				规格 (Dimensions): $\Phi_o20 \times \Phi_i10 \times h7\text{mm}$, 白色(White)					
适用温度范围(Temperature): 1650 °C ~ 1900 °C				试验条件(Condition): 保温 1 小时					
Φ (mm)	T (°C)	Φ (mm)	T (°C)	Φ (mm)	T (°C)	Φ (mm)	T (°C)	Φ (mm)	T (°C)
		18.50	1709	18.00	1765	17.50	1813	17.00	1863
		18.49	1710	17.99	1766	17.49	1814	16.99	1864
		18.48	1712	17.98	1767	17.48	1815	16.98	1865
		18.47	1713	17.97	1768	17.47	1816	16.97	1866
		18.46	1715	17.96	1769	17.46	1817	16.96	1867
		18.45	1716	17.95	1770	17.45	1818	16.95	1868
		18.44	1717	17.94	1771	17.44	1819	16.94	1869
		18.43	1718	17.93	1772	17.43	1820	16.93	1870
		18.42	1719	17.92	1773	17.42	1821	16.92	1871
		18.41	1721	17.91	1774	17.41	1822	16.91	1872
18.90	1649	18.40	1722	17.90	1775	17.40	1823	16.90	1873
18.89	1650	18.39	1723	17.89	1776	17.39	1824	16.89	1874
18.88	1651	18.38	1725	17.88	1777	17.38	1825	16.88	1875
18.87	1652	18.37	1726	17.87	1778	17.37	1826	16.87	1876
18.86	1653	18.36	1727	17.86	1779	17.36	1827	16.86	1877
18.85	1654	18.35	1729	17.85	1780	17.35	1828	16.85	1878
18.84	1655	18.34	1730	17.84	1780	17.34	1829	16.84	1879
18.83	1656	18.33	1731	17.83	1781	17.33	1830	16.83	1880
18.82	1657	18.32	1732	17.82	1782	17.32	1831	16.82	1881
18.81	1658	18.31	1733	17.81	1783	17.31	1831	16.81	1881
18.80	1660	18.30	1734	17.80	1784	17.30	1832	16.80	1882
18.79	1661	18.29	1735	17.79	1785	17.29	1833	16.79	1883
18.78	1663	18.28	1736	17.78	1786	17.28	1834	16.78	1884
18.77	1664	18.27	1737	17.77	1787	17.27	1835	16.77	1885
18.76	1666	18.26	1739	17.76	1788	17.26	1837	16.76	1886
18.75	1667	18.25	1740	17.75	1789	17.25	1838	16.75	1887
18.74	1668	18.24	1741	17.74	1790	17.24	1839	16.74	1888
18.73	1670	18.23	1742	17.73	1791	17.23	1840	16.73	1889
18.72	1672	18.22	1743	17.72	1792	17.22	1841	16.72	1890
18.71	1674	18.21	1744	17.71	1793	17.21	1842	16.71	1891
18.70	1676	18.20	1745	17.70	1793	17.20	1843	16.70	1892
18.69	1678	18.19	1746	17.69	1794	17.19	1843	16.69	1893
18.68	1679	18.18	1747	17.68	1795	17.18	1844	16.68	1894
18.67	1680	18.17	1748	17.67	1796	17.17	1845	16.67	1894
18.66	1682	18.16	1749	17.66	1797	17.16	1846	16.66	1895
18.65	1684	18.15	1750	17.65	1798	17.15	1847	16.65	1896
18.64	1686	18.14	1751	17.64	1799	17.14	1849	16.64	1897
18.63	1688	18.13	1752	17.63	1800	17.13	1850	16.63	1898
18.62	1690	18.12	1753	17.62	1801	17.12	1851	16.62	1899
18.61	1692	18.11	1754	17.61	1802	17.11	1852	16.61	1900
18.60	1693	18.10	1755	17.60	1803	17.10	1853		
18.59	1695	18.09	1756	17.59	1804	17.09	1854		
18.58	1696	18.08	1757	17.58	1805	17.08	1855		
18.57	1698	18.07	1758	17.57	1806	17.07	1856		
18.56	1700	18.06	1759	17.56	1807	17.06	1857		
18.55	1702	18.05	1760	17.55	1808	17.05	1858		
18.54	1703	18.04	1761	17.54	1809	17.04	1859		
18.53	1705	18.03	1762	17.53	1810	17.03	1860		
18.52	1706	18.02	1763	17.52	1811	17.02	1861		
18.51	1707	18.01	1764	17.51	1812	17.01	1862		

检验工程师 (Inspector): 黄满连

生产日期 (Date): 2023-03-21